


GALVANIZED WIRE ROPES | BALEA SEALE 6x19



Galvanized wire rope specially designed and manufactured to cover the highest expectations of fishing labours. It owns a great **flexibility**, and the special covering of the wires provides the wire rope with a **high corrosion resistance**.

The grease that we use in our fishing wire ropes is an oily grease specially indicated to endure sea water's temperature changes. Likewise, this grease has been conceived to persist in the wire rope for a **long period**, and to lubricate it while protecting for the marine corrosion.



BALEA SEALE 6x19 + IWRC

Diameter	Weight / mt	Breaking strength
14	0,78	12.654
16	1,02	16.206
18	1,29	20.202
19	1,47	23.199
20	1,59	25.863
22	1,93	30.525
23	2,11	32.523
24	2,29	35.964
26	2,69	42.069
28	3,12	50.061
30	3,58	52.276
32	4,08	64.935
34	4,62	70.818



BALEA SEALE 6x19 + FC

Diameter	Weight / mt	Breaking strength
14	0,72	11.400
16	0,93	14.600
18	1,17	18.200
19	1,33	20.900
20	1,49	23.300
22	1,79	27.500
23	1,87	29.300
24	2,07	32.400
26	2,46	37.900
28	2,88	45.100
30	3,31	51.600
32	3,82	58.500
34	4,31	63.800

*Dimensions are only for information purposes.