

BRAIDED ROPES | NYLON



Rope manufactured with high tenacity Polyamide fibres. Its neutral lay construction avoids turns when working. Due to its lack of buoyancy, this rope is frequently used in marine installations mooring. Likewise, its great tenacity and flexibility make this rope ideal for vessel mooring.

One of the properties of the Polyamide is its shrinkage capacity, whereby the durability of knots is much higher. For this reason, it is specially indicated for fishing nets.

CHARACTERISTICS

- **Material:** Polyamide (HT)
- **Construction:** 8, 12, 16 or 24 braided strands
- Excellent abrasion resistance
- Without buoyancy
- Good elasticity
- Good flexibility
- Excellent UV protection
- Very dynamic
- Neutral lay

Diameter	Weight (100m)	Breaking strength
6	2,25	760
8	4,00	1.390
10	6,20	2.130
12	8,90	3.040
14	12,20	4.180
16	15,80	5.380
18	20,00	6.880
20	24,50	8.450
22	30,00	10.400
24	35,50	12.300
26	42,00	14.500
28	48,50	16.200
30	55,50	18.300
32	63,00	20.600
34	71,40	23.200
36	80,00	25.700
38	89,30	28.200
40	99,00	31.000
42	109,0	33.800
44	120,0	37.000
45	124,8	37.800
48	142,0	43.000
50	153,5	46.300
52	166,0	50.000
55	186,2	55.000
56	193,0	57.000
60	221,0	64.500

*Dimensions are only for information purposes.

