

SEINE ROPE | DANISH SEINING



Combination rope of 3 or 4 strands, specifically designed for the Danish Seining. Due to its iKrome covering, it has an excellent abrasion resistance and low elongation.

We offer the option of a conic Seine rope: different diameters in the same length without splices.

LEADED SEINE ROPE 3 strands

Diameter	Weight (220m)	Breaking Strength
20	60	7.600
20	77	9.750
20	88	11.145
22	79	8.905
24	88	10.490
28	121	13.910
30	145	16.070
32	165	17.540
34	190	19.630
36	220	22.080
38	253	24.470

CHARACTERISTICS

- **Material:** lead or galvanized steel
- **Cover Material:** iKrome
- **Construction:** 3 or 4 strands
- **Optional:** conic Seine rope

- Excellent abrasion resistance
- Low elongation

*Dimensions are only for information purposes.



COMBINATION SEINE ROPE 4 strands

Diameter	Weight (220m)	Breaking Strength
18	77	5.500
20	85.8	7.600
22	90.2	8.100
24	118.8	8.700
26	128	9.200
26	150	10.500
28	137	15.500
28	150	16.800
30	159	17.500
32	194	18.500
34	220	19.000

Diameter	Weight (220m)	Breaking Strength
36	242	19.000
38	280	20.100
40	310	22.500
40	330	22.800
42	330	22.800
44	350	24.500
46	375	26.000
50	460	31.000
54	500	33.000
60	530	38.000