

SEINE ROPE | SMALLER VESSELS PURSE SEINING



Combination rope of 3 or 4 strands, specifically designed for the purse-sei

ning. Its special construction of hard lay, make this ropes ideal for the closure of the net through the rings.

In this combination ropes, it is a possibility to vary the amount of lead or steel to regulate the sinking speed.

COMBINATION SEINE ROPE

In the **combination seine rope** we offer the option of making both ends of the Seine Rope without steel.

Diameter	Weight (100m)
22	50
24	60
28	90
30	95
32	100
34	110
38	140

CHARACTERISTICS

- **Material:** leaded, unleaded or galvanized steel
- **Cover material:** Itsasplus
- **Construction:** 3 or 4 strands
- **Optional:** both ends without steel & different amount of lead or steel

- Excellent abrasion resistance
- Low elongation
- Hard lay

*Dimensions are only for information purposes.



LEADED SEINE ROPE

Diameter	Weight (100m)	Breaking Strength
26	30,50	12.320
28	35,50	13.910
30	40,50	16.070
32	46,00	17.540
34	52,00	19.520
36	58,50	22.080
38	65,00	24.150
40	72,00	26.860
42	79,00	28.950
44	88,00	31.780
46	96,00	33.850

> In the **leaded seine rope**, we offer the option to add extra lead.

UNLEADED SEINE ROPE

Diameter	Weight (100m)	Breaking Strength
26	34,50	12.320
28	41,50	13.910
30	46,00	16.070
32	53,00	17.540
36	68,00	22.080
40	83,00	26.860
44	101,00	31.780
48	119,50	37.180
52	140,50	43.195

> In the **leaded and unleaded seine ropes**, we offer the option of a conic Seine rope (different diameters in the same length without splices).