

HEADROPE | BOTTOM TRAWL



CLASSIC TARRED PP

4 strands combination rope, covered with tarred PP multifilaments. It is used in the construction of the bottom trawl net and it is fitted on the header section.

Diameter	Weight (100m)	Breaking strength
16	55	7.500
18	70	9.200
20	80	11.300
22	82	12.200
24	95	15.000
26	100	16.000
28	105	17.000
30	115	18.000

CHARACTERISTICS

- **Material:** galvanised steel
- **Cover material:** tarred Polypropylene
- **Construction:** 4 strands
- Without buoyancy
- Good UV protection
- Good abrasion resistance
- Low elongation

*Dimensions are only for information purposes.



TRaKTOR

Braided rope manufactured with high tenacity iKrome fibre, that passes a pre-stretched and thermofixing treatment, earning properties as low elongation and ease to handle. Due to its low weight and buoyancy, it allows to reduce the number of floats, decreasing the fuel consumption.

It can be covered with fibre to protect the material against abrasion, UV rays, and provide a better attachment surface.

Using this rope, we avoid the use of wire ropes, forgetting the corrosion problem, that is common when we use and stock the trawl repeatedly.

CHARACTERISTICS

- **Material:** iKrome (hT)
- **Cover material:** Itsasplus (optional)
- **Construction:** 12 braided strands
- Buoyancy
- Easy handling
- Good abrasion resistance
- Without corrosion
- Low elongation
- Pre-stretched
- Thermofixing treatment